

HI 151

## Folding Pocket Thermometer

- $\pm 0.3^{\circ}\text{C}$  accuracy
- CAL CHECK®
- Stainless steel folding probe with penetration tip
- Enables angled measurement
- Ergonomic
- Auto shut-off

The folding Checktemp®4 provides practical temperature measurement for the food service industry.

Special attention was given to the ergonomic form of Checktemp®4. This thermometer fits comfortably and securely in your hand. The LCD on the side of the handle is easy to see and read. The fast responding, fold-away probe is made of high quality, stainless steel and can penetrate semi-frozen and semi-solid foods like meats, ice cream and cheeses. When you are finished using your Checktemp®4, wipe the probe clean and fold it away. Checktemp®4 automatically turns OFF so you can safely carry it in your pocket.

### CAL CHECK®

As you unfold the stainless steel probe, the Checktemp® 4 automatically turns ON and immediately performs a calibration test. This unique HANNA feature, CAL CHECK®, provides the security of knowing you have accurate measurements. CAL CHECK® also lets you know if your battery level is low or if your meter requires recalibration.

### ORDERING INFORMATION

**HI 151-00** (Checktemp®4 C) is supplied complete with battery and instructions

**HI 151-01** (Checktemp®4 F) is supplied complete with battery and instructions

**HI 151-001** (Checktemp®4 C) is supplied complete with calibration certificate, battery and instructions

**HI 151-011** (Checktemp®4 F) is supplied complete with calibration certificate, battery and instructions

**HI 151-02** (Checktemp®4 C)  $\pm 0.5^{\circ}\text{C}$  accuracy, without CAL CHECK is supplied complete with battery and instructions



Contact us:

Chainaris Phuket Engineering Co., Ltd.

63/13 Moo.2, T.Vichit, A.Muang Phuket 83000

Tel: 076-513100-3

Fax: 076-513105

Line: @chainaris, @chainarissshop



Turns on and off by opening and closing the probe

SPECIFICATIONS	HI 151-00 (Checktemp®4C)	HI 151-01 (Checktemp®4F)
Range	-50.0 to 220°C	-58.0 to 428°F
Resolution	0.1°C (-50.0 to 199.9°C); 1°C (200 to 220°C)	0.1°F (-58.0 to 199.9°F); 1°F (200 to 428°F)
Accuracy	$\pm 0.3^{\circ}\text{C} \pm 1$ digit (-20.0 to 90.0°C); $\pm 1\%$ F.S. $\pm 1$ digit (outside)	$\pm 0.5^{\circ}\text{F} \pm 1$ digit (-4.0 to 194.0°F); $\pm 1\%$ F.S. $\pm 1$ digit (outside)
Calibration Check	automatic, at start-up	
Probe	stainless steel probe with penetration tip; 117 x dia 3.5 mm (4.6 x dia 0.14")	
Battery Type / Life	1.5V AA / approximately 25,000 hours of continuous use; auto-off after 8 minutes of non-use	
Environment	0 to 50°C (32 to 122°F); RH max 95%	
Dimensions	165 x 50 x 20 mm (6.5 x 2.0 x 0.8")	
Weight	100 g (3.5 oz.)	