

PENTEK® EPM SERIES

MODIFIED EPSILON CARBON BLOCK CARTRIDGES

ECONOMICALLY PRICED ODOR AND TASTE REDUCING FILTRATION



Pentair® Pentek® EPM Series Cartridges are a modified version of our EP Series Cartridge. An economical price makes this cartridge suitable for taste, odor and chlorine taste & odor reduction, as well as sediment filtration.*

EPM Series Cartridges are manufactured using a process that yields a cartridge with a nominal 10 micron filtration rating, high porosity and chlorine taste & odor reduction. The high porosity design helps prevent the cartridge from plugging before its adsorption capability is exhausted, maximizing the utilization of the carbon while maintaining low pressure drop.

These cartridges are protected by an outer wrap designed to significantly increase the useful life of the cartridge by trapping sediment that typically plugs carbon block cartridges.

FEATURES/BENEFITS

Nominal 10 micron rating*

Enhanced dirt holding capacity for extended cartridge life*

Lowest pressure drop

Bad taste and odor, and chlorine taste & odor reduction*

Economically priced

SPECIFICATIONS

Filter Media – Bonded PAC

Endcaps – Polypropylene

Outer Wrap – Polyolefin

Netting – Polyethylene

Gaskets – Buna-N

Temperature Rating –
40-180°F (4.4-82.2°C)



Tested and Certified by NSF International to NSF/ANSI Standard 42 for material requirements only.

* Based on manufacturer's internal testing.

SPECIFICATIONS AND PERFORMANCE

MODEL #	PART #	MAXIMUM DIMENSIONS	RATING (NOMINAL)*	INITIAL ΔP (PSI) @ FLOW RATE (GPM)*	CHLORINE TASTE & ODOR REDUCTION @ FLOW RATE (GPM)*
EPM-10	155634-43	2.88" x 9.75" (73 mm x 248 mm)	10 micron	1.5 psi @ 1 gpm (0.10 bar @ 3.8 Lpm)	>3,000 gallons @ 1 gpm (11,400L @ 3.8 Lpm)
EPM-20	155635-43	2.88" x 20" (73 mm x 508 mm)	10 micron	1.0 psi @ 2 gpm (0.07 bar @ 7.6 Lpm)	>6,000 gallons @ 2 gpm (22,700L @ 7.6 Lpm)
EPM-BB	155782-43	4.63" x 9.75" (118 mm x 248 mm)	10 micron	5.0 psi @ 2 gpm (0.35 bar @ 7.6 Lpm)	>15,000 gallons @ 2 gpm (56,750L @ 7.6 Lpm)
EPM-20BB	155783-43	4.63" x 20" (118 mm x 508 mm)	10 micron	4.0 psi @ 4 gpm (0.28 bar @ 15.1 Lpm)	>30,000 gallons @ 4 gpm (113,500L @ 15.1 Lpm)

*Based on manufacturer's internal testing.

NOTES: Performance capacity depends on system design, flow rate and certain other application conditions. Cartridges may contain a very small amount of carbon fines (very fine black powder). After installation, follow the instructions for flushing the cartridge to remove the fines before using the water. You should flush the tap at least 20 seconds prior to using water for drinking or cooking purposes. This is particularly important if the tap has not been used daily.

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



Contact us:

Chainaris Phuket Engineering Co., Ltd.

63/13 Moo.2, T.Vichit, A.Muang Phuket 83000

Tel: 076-513100-4 Fax: 076-513105

Line: @chainaris, @chainarissshop



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

310076 REV D AP14 © 2014 Pentair Residential Filtration, LLC All Rights Reserved.