

BRITESTREAM MKV MULTICOLOURED LED LIGHT

BriteStream Multicoloured LED light can produce myriad colours without the need for coloured lenses. In fact, there are nine different colour programs available.

- Energy saving operates on 15% of the energy of a halogen
- New BriteLUX diffuser lens
- Long life LEDs
- Universal adaptor plate
- Multi-Voltage, enabling connection to 12, 24 or 32 volt systems.









www.waterco.com



BriteLux Diffuser Lens

Unlike traditional LED lights that restrict the light output to individual hot spots, BriteLUX Diffuser Lens radiates light throughout the entire circumference of the lens.

In fact, the BriteLUX Diffuser Lens significantly boosts colour saturation and increases light transmission by 50 percent.

Multicoloured LED Light

The BriteStream Multicoloured LED light can produce nine different colour programs.

| WHITE | \bigcirc | RED | 0 |
|---|------------|--------------------------|------------|
| SLOW CHANGING COLOURS - 20 SECOND RAMPING | | YELLOW - GREEN (GOLD) | \bigcirc |
| FAST CHANGING COLOURS - 5 SECOND RAMPING | | GREEN | |
| BLUE | ٢ | AQUA | |
| MAGENTA | | | |

Easily replace your existing pool halogen lights.

Britestream Light can easily replace an existing halogen light as they can connected to 12, 24 or 32 volt systems, slashing your pool light electrical power requirements by 85%. Britestream LED Replacement Kit is supplied with two Retrofit Connector (IP68) and an Universal ¼ turn twist-lock adaptor plate.



Universal 1/4 Turn Twist-Lock Adaptor Plate

Universal 1/4 Turn Twist-Lock Adaptor Plate is designed to adapt the Britestream to the following light fittings.

- AQ Aquaquip
- SE Spa Elecrric
- SW Swim World
- PR Pool Rite
- ST Stroud

Technical Specifications

| Zonal | Power | Input Voltage | Input Voltage |
|---------------------|--------|--------------------|---------------------|
| Distribution | Usage | (New Installation) | (Replacement Light) |
| 0 to 180 degrees | 15Watt | 12V AC | |

Warranty

Britestream LED lights are covered by a comprehensive 2 Year warranty.

NSW - Sydney (Head Office) Tel: +61 2 9998 8600 QLD - Brisbane Tel: +61 7 3299 9900 VIC/TAS - Melbourne Tel: +61 3 9764 1211 WA - Perth Tel: +61 8 9273 1900 SA/NT - Adelaide Tel: +61 8 8244 6000 ACT Distribution Tel: +61 2 6280 6476 Waterco (Europe) Limited Sittingbourne, Kent. UK Tel: +44 (0) 1795 521 733 Waterco (USA) Inc Augusta, Georgia, USA Tel: +1 706 793 7291 Waterco Canada Longueuil, Quebec, Canada Tel: +1 450 748 1421 Waterco (NZ) Limited Auckland, New Zealand Tel: +64 9 525 7570

Waterco (C) Limited Guangzhou, China Tel: +86 20 3222 2180 Waterco (Far East) Sdn Bhd Selangor, Malaysia Tel: +60 3 6145 6000 PT Waterco Indonesia Jakarta, Indonesia Tel: +62 21 4585 1481 Waterco Singapore Intl Pte Ltd Nehsons Building, Singapore Tel: +86 544 2378

In the interest of providing better quality and value we are constantly improving and updating our products. Consequently, pictures and information on our brochures may sometimes vary slightly from models available.



BriteLux Diffuser Lens Its diffuser lens radiates the entire light and boosts light transmission.

Slotted Rims

Assists heat dissipation, as well as permitting water circulation.

Super Bright & Energy Saving

Super bright energy saving LEDs, which operate on only 15 watts of energy, which is 15% of the electrical power of a halogen light.

Long Life LEDs LEDs are long lasting,

energy efficient light source.

Built-in Heat Management

The LED's heat output is automatically managed by its electronic circuitry.

Pool Cleaner Shield


Improves the aesthetics of the installation and prevents the pool cleaner's skirt from being trapped behind the light.

Retrofit Connectors (IP68)

Easy to use Retrofit Connector, is supplied in two sizes, one that suits 6mm & less and another 6mm & plus power cable. Simply crimp both connections with the splice connectors, slide the cable sleeve over the connection and hand tighten the gland nuts.



Dimensions



DISTRIBUTED BY:

water, the liquid of life



SPASA